

Four-stroke Outboards

Model	F25	F20A	F15	F9.8	F6A	F5	F4	F2.6
Max. Power	25HP/18.4Kw	20HP/14.7Kw	15HP/11Kw	9.8HP/7.2Kw	6HP/4.4Kw	5HP/3.6Kw	4HP/2.9Kw	2.6HP/1.9Kw
Engine type	2-cyl. SOHC	2-cyl. SOHC	2-cyl. SOHC	2-cyl. SOHC	1-cyl. OHV	1-cyl. OHV	1-cyl. OHV	1-cyl. OHV
Displacement	498cc	362cc	323cc	209cc	148cc	112cc	112cc	72cc
Bore x Stroke	65.0x75.0mm 2.56x2.95in.	63.0x58.1mm 2.48x2.29in.	59.0x59.0mm 2.32x2.32in.	55.0x44.0mm 2.17x1.73in.	64.0x46.0mm 2.52x1.8in.	59.0x41.0mm 2.32x1.61in.	59.0x41.0mm 2.32x1.61in.	54.0x31.5mm 2.13x1.24in.
Max. RPM Range	5000~6000	5000~6000	4500~5500	5000~6000	4500~5500	4000~5000	4000~5000	5250~5750
Idling RPM Range	950~1050	1000~1100	1000~1100	900~1000	1450~1550	1500~1600	1500~1600	1550~1650
Sump Oil Capacity	1.7L	1.6L	1.0L	0.8L	0.8L	0.5L	0.5L	0.35L
Ignition System	C.D.I	C.D.I	C.D.I	C.D.I	C.D.I	T.C.I.	T.C.I.	T.C.I.
Starting System	Electric+Manual Or Manual	Electric+Manual Or Manual	Electric+Manual Or Manual	Electric+Manual Or Manual	Manual	Manual	Manual	Manual
Steering System	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller	Tiller	Tiller	Tiller
Trim and Tilt	Manual or Electric	Manual	Manual	Manual	Manual	Manual	Manual	Manual
Gear Shift	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N
Gear Ratio	2.08	2.08	2.08	2.08	2.15	2.08	2.08	2.08 or 2.25
Gear Oil Capacity	320cc	250cc	250cc	320cc	195cc	100cc	100cc	75cc
Transom Height	15in. or 20in.	15in. or 20in.	15in. or 20in.	15in. or 20in.	15in. or 20in.	15in. or 20in.	15in. or 20in.	15in. or 20in.
Dry Weight*	66kg	51.7kg	49kg	38kg	27kg	24.5kg	24.5kg	17kg
Alternator Output*	12V, 6A	12V, 6A	12V, 6A	12V, 6A	12V, 6A	None	None	None
Fuel Tank	24L	24L	24L	12L	Build-in 1.3L	Build-in 1.3L	Build-in 1.3L	Build-in 1.2L
Propeller* (pitch)	11.25" or 12"	8", 10", 11", 12"	8", 10", 11", 12"	8.3"	9"	6" or 7"	6" or 7"	6" or 5.38"

*Vary on models